

# DYNATRANS DA 85W90



## Data sheet

Oil for limited slip differentials self blocking axles

TOTAL

### APPLICATIONS

#### Limited slip differentials

- Oil specially adapted to the lubrication of self-blocking axles equipped with limited self-differentials.

### PERFORMANCES

#### International Specifications

- API GL-5
- ZF TE-ML 05C,12C

#### Level

- MIL-L-2105D

### CUSTOMER BENEFITS

#### Technical Profile

- High viscosity index
- Very high extreme-pressure properties
- Specific friction properties
- High thermal stability
- Excellent oxidation resistance, anti-wear, antifoam and antirust properties

### CHARACTERISTICS

| Total Dynatrans DA      | Method     | Units              | SAE Grade 85W90 |
|-------------------------|------------|--------------------|-----------------|
| Volumetric mass at 15°C | ASTM D1298 | Kg/m <sup>3</sup>  | 906             |
| Viscosity at 40°C       | ASTM D445  | mm <sup>2</sup> /s | 162             |
| Viscosity at 100°C      | ASTM D445  | mm <sup>2</sup> /s | 17              |
| Viscosity index         | ASTM D2270 | -                  | 108             |
| Flash point Cleveland   | ASTM D97   | °C                 | 188             |
| Pour point              | ASTM D92   | °C                 | -15             |

The typical characteristics mentioned represent mean values.

Total Dynatrans DA 85W90  
Version August, 2009

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.