

## Tru Grit RX Gear Oil 75w90 GL-4

### Description

**RX GEAR OIL 75W90** are a heavy duty automotive multi-purpose, sophisticated extreme pressure gear lubricant designed to meet the requirements of the API Service Classification GL-4. It is fully inhibited against foaming, oxidation and corrosion, and contains sulphur/phosphorous extreme pressure additives which ensure that the oil meets all the requirements of modern automotive differentials, manual transmissions and final drives to operate at high load-carrying capacity at sustained high speed under high torque loading conditions, where such gear oils are required.

### Applications

**RX GEAR OIL 75W90** should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this grade of gear oil (is recommended for 4WD gearboxes and transfer drives.)

### Specifications

**RX GEAR OIL 75W/90** meets or exceeds the following specifications:

API: GL-4

DAIMLER-CHRYSLER: 235.5, 235.1

MAN: 341 (EOD)

MILITARY SPECIFICATIONS: MIL-L-2105D

ZF: TE-ML02, TE-ML08

### Typical Physical Characteristics

Property	Typical Value
SAE Grade	75W90
Density, kg/L	0.881
Colour	2.5
Kinematic Viscosity at 40Deg C, cSt	142
Kinematic Viscosity at 100Deg C, cSt	16.78
Viscosity Index	126
Phosphorous, %wt	0.04

Revision 1.1	Issued: 30/08/2011 Revised: 29/8/2011	Page 1 of 1
--------------	--	-------------