



TOTAL

TOTAL QUARTZ 9000 FUTURE GF5 5W-30

Motor Oil

BASICS

PASSENGER CAR RANGE



INTERNATIONAL SPECIFICATIONS

- ✓ API SN
- ✓ API CF performance level
- ✓ ILSAC GF-5

Engine Motor Oil

SAE 5W-30

SYNTHETIC TECHNOLOGY

APPLICATIONS

TOTAL QUARTZ 9000 FUTURE GF5 5W-30 is developed to meet the requirements of gasoline engines. It is particularly suited to turbocharged, multi-valve and direct injection engines.

TOTAL QUARTZ 9000 FUTURE GF-5 is formulated as full synthetic engine oils to provide excellent oxidation stability, low temperature flow properties, enhanced fuel economy and extended drain.

TOTAL QUARTZ 9000 FUTURE GF5 5W-30 is an all-season synthetic oil that can be used under the most difficult operating conditions (highways, congested city traffic, etc...). It is perfectly adapted to all vehicles equipped with catalysts using unleaded fuel or LPG (liquefied petroleum gas)

CLIENTS BENEFITS

- The product enhances **the engine performance**
- This product could be used for all high performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies
- This product is designed to improve **the fuel economy efficiency**
- **Protection of three way catalyst poisons** by reducing the volatility of the phosphorus in the lubricant, a poison of the post-treatment devices
- A robust oil film which resists oxidation at high temperature and allows extended drain intervals
- High quality detergents and dispersants keep engine parts clean.

CHARACTERISTICS*

Tests	Unit	Test method	
Grade	-	SAE J300	5W-30
Density at 15 °C	kg/m ³	ASTM D1298	8504
Kinematic viscosity at 40 °C	mm ² /s	ASTM D445	57
Kinematic viscosity at 100 °C	mm ² /s	ASTM D445	10
Viscosity index	-	ASTM D2270	160
Pour point	°C	ASTM D97	-36
Flash point COC	°C	ASTM D92	235

*The characteristics given above are obtained a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance manual should be checked: oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the barrels should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.