



# RUBIA CF-2 40



*Monograde lubricant for two stroke Diesel engines*

## SPECIFICATIONS

<b>International specifications</b>	<b>API CF-2/CF</b>	<b>MIL.L. 46152B</b>
-------------------------------------	--------------------	----------------------

### Meets the requirements of

- ✓ Detroit Diesel : Oil typ 1 and 2 for series : 53, 71, 92, 110 and 149 marine

## APPLICATIONS

This lubricant is suitable for all two stroke Diesel engines when API CF-2 or API CD II specifications are required.

**TOTAL RUBIA CF-2 40** has been especially developed for the lubrication of two stroke Detroit Diesel engines.

It also can be used in Diesel or gasoline engines of old vehicles.

## PERFORMANCES AND CUSTOMER BENEFITS

- Good anti-wear and anti-corrosion properties
- Excellent anti-oxidation properties allowing long time idle or very severe working conditions (hot climates, heavy load...)
- Low ash value ensuring good engine cleanliness
- Very high performance detergent and dispersant additives

## PHYSICAL AND CHEMICAL CHARACTERISTICS\*

<b>TOTAL RUBIA CF-2 40</b>		<b>Method</b>	<b>Value</b>
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	145.9
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	14.5
Viscosity Index	-	ASTM D2270	98
T.B.N	mgKOH/g	ASTM D2896	7.1
Pour Point	°C	ASTM D97	-15
Sulphated Ash	% m/m	ASTM D874	0.77

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

**TOTAL LUBRIFIANTS**  
562, avenue du Parc de l'Île  
92029 Nanterre cedex  
FRANCE

**TOTAL RUBIA CF-2 40**  
Update 11/2014  
[www.lubricants.total.com](http://www.lubricants.total.com)



This lubricant does not cause adverse health effects when used in the intended application.  
A safety datasheet is accessible on request from your local dealer or on the website [www.quickfds.com](http://www.quickfds.com)