

# RUBIA S

10W



TOTAL

**Diesel engine type lubricant for hydraulic applications**

## UTILISATION

- Recommended for hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

## PERFORMANCES

Specifications

API

CF/SF

## CUSTOMER BENEFITS

Technical performances

- Monograde
- High viscosity index
- High stability in operation
- Exceptional detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Excellent antioxydant, antirust and antifoaming properties

## CHARACTERISTICS

Rubia 4400	Units	SAE Grade <b>10W</b>
Volumetric mass at 15°C	kg/m <sup>3</sup>	881
Viscosity at 100°C	mm <sup>2</sup> /s	5.8
Viscosity index	-	100
Flash point	°C	>200
Pour point	°C	-33
T.B.N	mgKOH/g	11.2

*The typical characteristics mentioned represent mean values.*

TOTAL LUBRIFIANTS  
562 avenue du Parc de L'île  
92029 NANTERRE Cedex  
France

RUBIA S 10W  
FEBRUARY 2013



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.