

# RUBIA XT

## 15W-40



**Multigrade oil for diesel engine**

### UTILISATION

- Developed for all Diesel engines, turbocharged or not, in severe service conditions in all seasons.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).

### PERFORMANCES

#### Specifications

ACEA E2  
API CF-4/SJ

#### OEMS' approvals

MERCEDES MB-Approval 228.1  
MAN 271  
VOLVO VDS  
MIL-L 2104 E

### CUSTOMER BENEFITS

#### Performances techniques

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- High dispersancy level
- Excellent antiwear and anticorrosion properties
- Very good anti oxydant, antirust and antifoam properties.

### CHARACTERISTICS

	Units	SAE grade <b>15W-40</b>
Volumetric mass at 15°C	kg/m <sup>3</sup>	887
Viscosity at 100°C	mm <sup>2</sup> /s	13.9
Viscosity index	-	131
Flash Point	°C	>200
Pour point	°C	-30
T.B.N	mgKOH/g	9.2

*The typical characteristics mentioned represent mean values.*

#### TOTAL LUBRIFIANTS

Le SPAZIO  
562 Avenue du Parc de l'île  
92029 - NANTERRE CEDEX

**RUBIA XT 15W-40**  
**May 2009**  
**N° MPR 05/09**



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.