

TRU GRIT AC – 26 Brake Fluid

Description

TRU GRIT AC-26 is an inhibited glycol ether blend meeting the requirements of a general purpose hydraulic brake fluid of average performance.

It is specifically designed for the low to medium performance modern car as well as older cars with low heat load around the braking system.

In the absence of specific instructions by the vehicle manufacturer, it is recommended that the fluid be replaced every twelve months under average driving conditions.

Performance of AC26 significantly exceeds:

FMV SS 116, DOT 3

As well as:

Australian Standards AS/NZS 1960—1995 Grade 1 & SAE J1703

Applications

Is suitable for Toyota and some other Japanese Manufactured vehicles.

Typical Physical Characteristics

Appearance: Amber liquid

pH 9.7

Odour: Slight Odour

Flammable: Class C1 Combustible

ER Boiling Point: NA

Solubility: Soluble

Flash Point: N/A

Reserve Alkalinity: 52.00

Directions for Use

1. Clean and flush system prior to refilling
2. Add fluid in accordance to vehicle manufacturer's recommendation.
3. Reseal container immediately after to avoid contamination and absorption of moisture.

IMPORTANT:

- * Do not allow contact with paintwork.
- * Do not mix brake fluids.
- * Dispose of empty containers properly. Do not use empty container for storing other fluids.